Safety Data Sheet according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# ARCAL<sup>TM</sup>Speed, ARCAL<sup>TM</sup>21 Issue date: 9/23/2009 Revision date: 4/15/2024 Supersedes version of: 4/24/2019 Version: 4.0

SDS reference: 2009483



### Warning

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Trade name	: ARCAL™Speed, ARCAL™21
SDS no	2009483
1.2. Relevant identified uses of the subs	tance or mixture and uses advised against
Relevant identified uses	: Industrial and professional use for chemical analysis, calibration, (routine) quality control,
	laboratory use, under controlled conditions.
	Perform risk assessment prior to use.
Uses advised against	: Consumer use.
	Uses other than those listed above are not supported, contact your supplier for more information on other uses.
1.3. Details of the supplier of the safety	data sheet
Company identification	AIR LIQUIDE SINGAPORE PTE LTD
	HEAD OFFICE : 2 VENTURE DRIVE, VISION EXCHANGE, #22-28, SINGAPORE 608526
	T +65 6265 3788 - F +65 6 265 1441
	Sg-info@airliquide.com - https://sg.airliquide.com/resources/safety-data-sheets-sds
1.4 Emorgonou tolophono number	
1.4. Emergency telephone number	
Emergency telephone number	: +65 6265 3788, +65 9619 9229 (After Office Hour)

### **SECTION 2: Hazards identification**

Air Liquide

### 2.1. Classification of the substance or mixture

Classification according	o Regulation (EC) No. 1272/2008 [CLP]
Physical hazards	Gases under pressure : Compressed gas H280
2.2. Label elements	
Labelling according to R	gulation (EC) No. 1272/2008 [CLP]
Hazard pictograms (CLP)	GHS04
Signal word (CLP)	: Warning
Hazard statements (CLP)	: H280 - Contains gas under pressure; may explode if heated.
Precautionary statements	CLP)
- Storage	: P403 - Store in a well-ventilated place.



ARCAL<sup>™</sup>Speed, ARCAL<sup>™</sup>21

Reference number: 2009483

### 2.3. Other hazards

: Asphyxiant in high concentrations. Not classified as PBT or vPvB. The substance/mixture has no endocrine disrupting properties.

### **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Argon	CAS-No.: 7440-37-1 EC-No.: 231-147-0 EC Index-No.: REACH-no: *1	92	Press. Gas (Comp.), H280
Carbon dioxide	CAS-No.: 124-38-9 EC-No.: 204-696-9 EC Index-No.: REACH-no: *1	8	Press. Gas (Liq.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

- Inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact	: Adverse effects not expected from this product.
- Eye contact	: Adverse effects not expected from this product.
- Ingestion	: Ingestion is not considered a potential route of exposure.
4.2. Most important symptoms	and effects, both acute and delayed
	: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.
	Low concentrations of CO2 cause increased respiration and headache.
	See section 11.
4.3. Indication of any immedia	te medical attention and special treatment needed
	: None.

### **SECTION 5: Firefighting measures**

ARCAL<sup>™</sup>Speed, ARCAL<sup>™</sup>21

Reference number: 2009483

5.1. Extinguishing media		
- Suitable extinguishing media	: Water spray or fog.	
	Product does not burn, use fire control measures appropriate for the surrounding fire.	
- Unsuitable extinguishing media	: Do not use water jet to extinguish.	
5.2. Special hazards arising from the substa	e or mixture	
Specific hazards	: Exposure to fire may cause containers to rupture/explode.	
Hazardous combustion products	: None.	
5.3. Advice for firefighters		
Specific methods	: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.	
	If possible, stop flow of product.	
	Use water spray or fog to knock down fire fumes if possible.	
	Move containers away from the fire area if this can be done without risk.	
Special protective equipment for fire fighters	: In confined space use self-contained breathing apparatus.	
	Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.	
	Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.	
	Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.	

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	<ul> <li>Act in accordance with local emergency plan.</li> <li>Try to stop release.</li> <li>Evacuate area.</li> <li>Ensure adequate air ventilation.</li> <li>Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.</li> <li>Stay upwind.</li> <li>See section 8 of the SDS for more information on personal protective equipment</li> </ul>	
For emergency responders	<ul> <li>Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.</li> <li>Oxygen detectors should be used when asphyxiating gases may be released.</li> <li>See section 5.3 of the SDS for more information.</li> </ul>	
6.2. Environmental precautions		
	: Try to stop release.	
6.3. Methods and material for containment and cleaning up		
	: Ventilate area.	
6.4. Reference to other sections		
	: See also sections 8 and 13.	

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

### ARCAL<sup>™</sup>Speed, ARCAL<sup>™</sup>21

Safe use of the product	: The product must be handled in accordance with good industrial hygiene and safety procedures.
	Only experienced and properly instructed persons should handle gases under pressure.
	Consider pressure relief device(s) in gas installations.
	Ensure the complete gas system was (or is regularily) checked for leaks before use.
	Do not smoke while handling product.
	Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
	Avoid suck back of water, acid and alkalis.
	Do not breathe gas.
	Avoid release of product into work area.
Safe handling of the gas receptacle	: Refer to supplier's container handling instructions.
	Do not allow backfeed into the container.
	Protect containers from physical damage; do not drag, roll, slide or drop.
	When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
	Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
	If user experiences any difficulty operating valve discontinue use and contact supplier.
	Never attempt to repair or modify container valves or safety relief devices.
	Damaged valves should be reported immediately to the supplier.
	Keep container valve outlets clean and free from contaminants particularly oil and water.
	Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
	Close container valve after each use and when empty, even if still connected to equipment.
	Never attempt to transfer gases from one cylinder/container to another.
	Never use direct flame or electrical heating devices to raise the pressure of a container.
	Do not remove or deface labels provided by the supplier for the identification of the content of the container.
	Suck back of water into the container must be prevented.
	Open valve slowly to avoid pressure shock.
7.2. Conditions for safe storage, includin	g any incompatibilities
	: Observe all regulations and local requirements regarding storage of containers.
	Containers should not be stored in conditions likely to encourage corrosion.
	Container valve guards or caps should be in place.
	Containers should be stored in the vertical position and properly secured to prevent them from falling over.
	Stored containers should be periodically checked for general condition and leakage.
	Keep container below 50°C in a well ventilated place.
	Store containers in location free from fire risk and away from sources of heat and ignition.
	Keep away from combustible materials.

### 7.3. Specific end use(s)

: None.

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Carbon dioxide (124-38-9)		
OEL : Occupational Exposure	Limits	
ACGIH	ACGIH OEL TWA [ppm]	5000 ppm
	ACGIH OEL STEL [ppm]	30000 ppm

### ARCAL<sup>™</sup>Speed, ARCAL<sup>™</sup>21

Reference number: 2009483

Remark (ACC	IH)	TLV® Basis: Asphyxia
DNEL (Derived-No Effect Level)	: None available.	
PNEC (Predicted No-Effect Concentration)	: None available.	
8.2. Exposure controls		
8.2.1. Appropriate engineering controls		
	: Provide adequate general a	and local exhaust ventilation.
	Oxygen detectors should b	e used when asphyxiating gases may be released.
	Systems under pressure s	hould be regularily checked for leakages.
	Ensure exposure is below of	occupational exposure limits (where available).
	Consider the use of a work	permit system e.g. for maintenance activities.
	CO2 detectors should be u	sed when CO2 may be released.
8.2.2. Individual protection measures, e.g.	personal protective equipment	
	related to the use of the pro following recommendations	be conducted and documented in each work area to assess the risk oduct and to select the PPE that matches the relevant risk. The s should be considered: nmended EN/ISO standards should be selected.
Eye/face protection	: Wear safety glasses with s Standard EN 166 - Persona	ide shields. al eye-protection - specifications.
Skin protection		
- Hand protection	: Wear working gloves when	handling gas containers.
	Standard EN 388 - Protecti	ve gloves against mechanical risks, performance level 1 or higher.
- Other	: Wear safety shoes while ha Standard EN ISO 20345 - I	andling containers. Personal protective equipment - Safety footwear.
<ul> <li>Respiratory protection</li> </ul>	expected, e.g. during main Standard EN 137 - Self-cor face mask. When indicated by a risk as selection of the Respiratory	oparatus is recommended, where unknown exposure may be tenance activities on installation systems. Intained open-circuit compressed air breathing apparatus with full essessment, Respiratory Protective Equipment must be used. The reprotective Device (RPD) must be based on known or anticipated ds of the product and the safe working limits of the selected RPD.
Thermal hazards	: None in addition to the abo	ve sections.
8.2.3. Environmental exposure controls		
-	: None necessary.	

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance	
<ul> <li>Physical state at 20°C / 101.3kPa</li> </ul>	: Gas.
- Colour	: Colourless.
Odour	: Odourless.
Melting point / Freezing point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
	It is technically not possible to determine the boiling point or range of this mixture. Component
	with lowest boiling point: Argon -186 °C
Flammability	: Non flammable.
Lower explosion limit	: Not available

### ARCAL<sup>™</sup>Speed, ARCAL<sup>™</sup>21

Reference number: 2009483

Upper explosion limit	: Not available
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
рН	: Not applicable for gases and gas mixtures.
Viscosity, kinematic	: No reliable data available.
Water solubility [20°C]	: Mixture is partially soluble in water
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for gas mixtures.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density and/or relative density	: Not applicable.
Relative vapour density (air=1)	: Heavier than air.
Particle characteristics	: Not applicable for gases and gas mixtures.

### 9.2. Other information

# 9.2.1. Information with regard to physical hazərb classes Explosive properties : Not applicable. Explosion limits : Non flammable. Oxidising properties : Not applicable. 9.2.2. Other safety characteristics : Not applicable for gas mixtures. Molar mass : Not applicable for gases and gas mixtures. Evaporation rate : Not applicable for gases and gas mixtures. Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

### **SECTION 10: Stability and reactivity**

10.1. Reactivity	
	: No reactivity hazard other than the effects described in sub-sections below. Data for mixtures are not available.
10.2. Chemical stability	
	: Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	: None.
10.4. Conditions to avoid	
	: Avoid moisture in installation systems.
10.5. Incompatible materials	
	: For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

<u>11.1. Information on toxicological effects</u> Acute toxicity	: Toxicological effects not expected from this product if occupational exposure limit values are not exceeded.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.

ARCAL<sup>™</sup>Speed, ARCAL<sup>™</sup>21

Reference number: 2009483

Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.
11.2. Information on other hazards	
Other information	: For more information, see 'EIGA Safety Info 24: Carbon Dioxide, Physiological Hazards' at www.eiga.eu.
	Unlike simple asphyxiants, carbon dioxide has the ability to cause death even when normal oxygen levels (20-21%) are maintained. 5% CO2 has been found to act synergistically to increase the toxicity of certain other gases (CO, NO2). CO2 has been shown to enhance the production of carboxy- or met-hemoglobin by these gases possibly due to carbon dioxide's stimulatory effects on the respiratory and circulatory systems.
	The substance/mixture has no endocrine disrupting properties.

### 12.1. Toxicity

Assessment	: No data available.
EC50 48h - Daphnia magna [mg/l] EC50 72h - Algae [mg/l] LC50 96 h - Fish [mg/l]	<ul> <li>No data available.</li> <li>No data available.</li> <li>No data available.</li> </ul>
12.2. Persistence and degradability	
Assessment	: No data available.
12.3. Bioaccumulative potential	
Assessment	: No data available.
<u>12.4. Mobility in soil</u>	
Assessment	: Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
12.5. Results of PBT and vPvB assessment	
Assessment	: No data available. Not classified as PBT or vPvB.
12.6. Endocrine disrupting properties	
Assessment	: The substance/mixture has no endocrine disrupting properties.
12.7. Other adverse effects Other adverse effects	: No known effects from this product.
Effect on the ozone layer	: Norking the strength in the product.
Effect on global warming	: Contains greenhouse gas(es).

### **SECTION 13: Disposal considerations**

ARCAL<sup>™</sup>Speed, ARCAL<sup>™</sup>21

Reference number: 2009483

13.1. Waste treatment methods	
	: May be vented to atmosphere in a well ventilated place.
	Do not discharge into any place where its accumulation could be dangerous.
	Return unused product in original container to supplier.
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.
13.2. Additional information	
	: External treatment and disposal of waste should comply with applicable local and/or national regulations.

## **SECTION 14: Transport information**

UN-No.	: 1956
14.2. UN proper shipping name	
Transport by road/rail (ADR/RID)	COMPRESSED GAS, N.O.S. (Argon, Carbon dioxide)
Transport by air (ICAO-TI / IATA-DGR)	Compressed gas, n.o.s. (Argon, Carbon dioxide)
Transport by sea (IMDG)	COMPRESSED GAS, N.O.S. (Argon, Carbon dioxide)
14.3. Transport hazard class(es)	
Labelling	
	2.2 : Non-flammable, non-toxic gases.
Transport by road/rail (ADR/RID)	
Class	: 2
Classification code	: 1A
Hazard identification number	: 20
Tunnel Restriction	: E - Passage forbidden through tunnels of category E
Transport by air (ICAO-TI / IATA-DGR)	
Class / Div. (Sub. risk(s))	: 2.2
Transport by sea (IMDG)	
Class / Div. (Sub. risk(s))	: 2.2
Emergency Schedule (EmS) - Fire Emergency Schedule (EmS) - Spillage	: F-C : S-V
14.4. Packing group	. 5-v
Transport by road/rail (ADR/RID)	: Not applicable
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable
Transport by sea (IMDG)	: Not applicable
14.5. Environmental hazards	
Transport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Transport by sea (IMDG)	: None.

EN (English)

14.6. Special precautions for user	
Packing Instruction(s)	
Transport by road/rail (ADR/RID)	: P200
Transport by air (ICAO-TI / IATA-DGR)	
Passenger and Cargo Aircraft	: 200.
Cargo Aircraft only	: 200.
Transport by sea (IMDG)	: P200
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment.
	Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
	Before transporting product containers:
	- Ensure there is adequate ventilation.
	- Ensure that containers are firmly secured.
	- Ensure valve is closed and not leaking.
	- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
	- Ensure valve protection device (where provided) is correctly fitted.
14.7. Transport in bulk according to Anne	x II of Marpol and the IBC Code

: Not applicable.

SECTION 15: Regulatory information	
15.1. Safety, health and environmental regu	lations/legislation specific for the substance or mixture
EU-Regulations	
Seveso Directive : 2012/18/EU (Seveso III)	: Not covered.
National regulations	
Regulatory reference	: Ensure all national/local regulations are observed.
15.2. Chemical safety assessment	
	: A CSA does not need to be carried out for this product.
SECTION 16: Other information	

Indication of changes

: Safety data sheet in accordance with commission regulation (EU) No 2020/878.



ARCAL<sup>™</sup>Speed, ARCAL<sup>™</sup>21

Reference number: 2009483

Abbreviations and acronyms	: ATE - Acute Toxicity Estimate
	CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
	REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
	EINECS - European Inventory of Existing Commercial Chemical Substances
	CAS# - Chemical Abstract Service number
	PPE - Personal Protection Equipment
	LC50 - Lethal Concentration to 50 % of a test population
	RMM - Risk Management Measures
	PBT - Persistent, Bioaccumulative and Toxic
	vPvB - Very Persistent and Very Bioaccumulative
	STOT- SE : Specific Target Organ Toxicity - Single Exposure
	CSA - Chemical Safety Assessment
	EN - European Standard
	UN - United Nations
	ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
	IATA - International Air Transport Association
	IMDG code - International Maritime Dangerous Goods
	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
	WGK - Water Hazard Class
	STOT - RE : Specific Target Organ Toxicity - Repeated Exposure
	UFI : Unique Formula Identifier
Training advice	: Receptacle under pressure.
	The hazard of asphyxiation is often overlooked and must be stressed during operator training.
	For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at http://www.eiga.eu
Further information	: Classification using data from databases maintained by the European Industrial Gases Association (EIGA). Data is maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at : http://www.eiga.eu.
	Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).
Full text of H- and EUH-statements	
H280	Contains gas under pressure; may explode if heated.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.