# Safety Data Sheet according to Regulation (EU) 2015/830



# LASAL<sup>™</sup>68

Date of issue: 12/01/2018 SDS reference: 2018005

- Supersedes: 12/01/2018
- Revision date: 24/04/2019

Version: 0.1



## Warning

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Trade name	: LASAL™68
SDS no	: 2018005
1.2. Relevant identified uses of the substan	ce or mixture and uses advised against
Relevant identified uses	: Industrial and professional. Perform risk assessment prior to use.
	Contact supplier for more information on uses.
Uses advised against	: Consumer use.
1.3. Details of the supplier of the safety data	<u>a sheet</u>
Company identification	: AIR LIQUIDE SINGAPORE PTE LTD HEAD OFFICE : 2 VENTURE DRIVE, VISION EXCHANGE, #22-28, SINGAPORE 608526 SPECIALGASES OFFICE, NO 24 JALAN BUROH SINGAPORE 619480 T +65 6 265 3788 https://industry.airliquide.sg/resources/safety-data-sheets-sds Sg-info@airliquide.com
1.4. Emergency telephone number	
Emergency telephone number	: +65 6265 3788, +65 9619 9229 (After Office Hour)

#### **SECTION 2: Hazards identification**

2.1. Classification of the	substance or mixture		
Classification according	to Regulation (EC) No. 1272/2008 [CLP]		
Physical hazards	Gases under pressure : Compressed gas	H280	
2.2. Label elements			
Labelling according to Re	egulation (EC) No. 1272/2008 [CLP]		
Hazard pictograms (CLP)	GHS04		
Signal word (CLP)	: Warning		
Hazard statements (CLP)	: H280 - Contains gas under pro	essure; may explode if heated.	
Precautionary statements (	CLP)		
	- Storage : P410+P403 - Protect from sur	light. Store in a well-ventilated place.	
AIR LIQUIDE SINGAPORE PT	E LTD EN (English)	SDS Ref.: 2018005	1/10



#### 2.3. Other hazards

: Asphyxiant in high concentrations.

In high concentrations CO2 cause rapid circulatory insufficiency. Symptoms are headache, nausea and vomiting, which may lead to unconsciousness.

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances : Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Helium	(CAS-No.) 7440-59-7 (EC-No.) 231-168-5 (EC Index-No.) (REACH-no) *1	66	Press. Gas (Comp.), H280
Nitrogen	(CAS-No.) 7727-37-9 (EC-No.) 231-783-9 (EC Index-No.) (REACH-no) *1	29	Press. Gas (Comp.), H280
Carbon dioxide	(CAS-No.) 124-38-9 (EC-No.) 204-696-9 (EC Index-No.) (REACH-no) *1	5	Press. Gas (Liq.), H280

Full text of H-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*2: Registration deadline not expired.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

- Inhalation	<ul> <li>Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.</li> </ul>	
- Skin contact	: Adverse effects not expected from this product.	
- Eye contact	: Adverse effects not expected from this product.	
- Ingestion	: Ingestion is not considered a potential route of exposure.	
4.2. Most important symptoms and effects, both acute and delayed		
	: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.	
	Low concentrations of CO2 cause increased respiration and headache.	

Refer to section 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed



SDS Ref.: 2018005

: None.

<b>SECTION 5: Firefighting measures</b>	
5.1. Extinguishing media	
- Suitable extinguishing media	: Water spray or fog.
- Unsuitable extinguishing media	: Do not use water jet to extinguish.
5.2. Special hazards arising from the substa	nce or mixture
Specific hazards	: Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products	: None.
5.3. Advice for firefighters	
Specific methods	: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
	If possible, stop flow of product.
	Use water spray or fog to knock down fire fumes if possible.
	Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	: In confined space use self-contained breathing apparatus.
	Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
	Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.
	Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

	: Try to stop release.
	Evacuate area.
	Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
	Ensure adequate air ventilation.
	Oxygen detectors should be used when asphyxiating gases may be released.
	Act in accordance with local emergency plan.
	Stay upwind.
6.2. Environmental precautions	
	: Try to stop release.
6.3. Methods and material for containment and	cleaning up
	: Ventilate area.
	Keep area evacuated and free from ignition sources until any spilled liquid has evaporated (ground free from frost).
6.4. Reference to other sections	
	: See also sections 8 and 13.



## **SECTION 7: Handling and storage**

7.1. Precautions for safe handling	
Safe use of the product	: The product must be handled in accordance with good industrial hygiene and safety procedures.
	Only experienced and properly instructed persons should handle gases under pressure.
	Consider pressure relief device(s) in gas installations.
	Ensure the complete gas system was (or is regularily) checked for leaks before use.
	Do not smoke while handling product.
	Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
	Avoid suck back of water, acid and alkalis.
	Do not breathe gas.
	Avoid release of product into atmosphere.
Safe handling of the gas receptacle	: Refer to supplier's container handling instructions.
	Do not allow backfeed into the container.
	Protect cylinders from physical damage; do not drag, roll, slide or drop.
	When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
	Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
	If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.
	Never attempt to repair or modify container valves or safety relief devices.
	Damaged valves should be reported immediately to the supplier.
	Keep container valve outlets clean and free from contaminants particularly oil and water.
	Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
	Close container valve after each use and when empty, even if still connected to equipment.
	Never attempt to transfer gases from one cylinder/container to another.
	Never use direct flame or electrical heating devices to raise the pressure of a container.
	Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.
	Suck back of water into the container must be prevented.
	Open valve slowly to avoid pressure shock.
7.2. Conditions for safe storage, including	ng any incompatibilities
	: Observe all regulations and local requirements regarding storage of containers.
	Containers should not be stored in conditions likely to encourage corrosion.
	Container valve guards or caps should be in place.
	Containers should be stored in the vertical position and properly secured to prevent them from falling over.
	Stored containers should be periodically checked for general condition and leakage.
	Keep container below 50°C in a well ventilated place.
	Store containers in location free from fire risk and away from sources of heat and ignition.
	Keep away from combustible materials.
7.3. Specific end use(s)	

: None.

## **SECTION 8: Exposure controls/personal protection**



#### 8.1. Control parameters

Carbon dioxide (124-38-9)			
OEL : Occupational Exposu	re Limits		
ACGIH	ACGIH TWA (ppm)		5000 ppm
	ACGIH STEL (ppm)		30000 ppm
	Remark (ACGIH)		Asphyxia
	Regulatory reference	ce	ACGIH 2017
DNEL (Derived-No Effect Le	evel) :	None available.	
PNEC (Predicted No-Effect	Concentration) :	None available.	
8.2. Exposure controls			
8.2.1. Appropriate enginee	ering controls		
	:	Provide adequate general and loca	l exhaust ventilation.
		Oxygen detectors should be used v	when asphyxiating gases may be released.
		Systems under pressure should be	e regularily checked for leakages.
		, ,	onal exposure limits (where available).
			system e.g. for maintenance activities.
			system e.g. for maintenance activities.
8.2.2. Individual protection			
	:	related to the use of the product an following recommendations should	ucted and documented in each work area to assess the risk d to select the PPE that matches the relevant risk. The be considered: d EN/ISO standards should be selected.
Eye/face protection	:	Wear safety glasses with side shiel Standard EN 166 - Personal eye-pr	
Skin protection			
- Hand protection	:	Wear working gloves when handling	g gas containers.
		Standard EN 388 - Protective glove	es against mechanical risk.
- Other	:	Wear safety shoes while handling of Standard EN ISO 20345 - Personal	containers. I protective equipment - Safety footwear.
<ul> <li>Respiratory protection</li> </ul>	:	used in oxygen-deficient atmosphe Standard EN 137 - Self-contained of face mask. Gas filters may be used if all surrou contaminant(s) and duration of use Use gas filters with full face mask, w period, e.g. connecting or disconne Gas filters do not protect against ow	open-circuit compressed air breathing apparatus with full unding conditions e.g. type and concentration of the are known. where exposure limits may be exceeded for a short-term acting containers.
Thermal hazards	:	None in addition to the above section	ons.
8.2.3. Environmental expo	sure controls		
· · · · · · · · · · · · · · · · · · ·		None necessary.	
	•	Hono noocooury.	

## **SECTION 9: Physical and chemical properties**



#### 9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C / 101.3kPa	: Gas
Colour	: Mixture contains one or more component(s) which have the following colour(s): Colourless.
Odour	: Odourless.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
рН	: Not applicable for gases and gas mixtures.
Melting point / Freezing point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
Flash point	: Not applicable for gases and gas mixtures.
Evaporation rate	: Not applicable for gases and gas mixtures.
Flammability (solid, gas)	: Non flammable.
Explosive limits	<sup>:</sup> Non flammable.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Vapour density	: Not applicable.
Relative density, gas (air=1)	: No reliable data available
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
Viscosity, kinematic	: No reliable data available.
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
9.2. Other information	
Molar mass	: Not applicable for gas mixtures.
Other data	: None.

# **SECTION 10: Stability and reactivity**

SINGAPORE 619480 +65 6 265 3788

10.1. Reactivity	
10.2. Chemical stability	: No reactivity hazard other than the effects described in sub-sections below.
	: Stable under normal conditions.
10.3. Possibility of hazardous reactions	: None.
10.4. Conditions to avoid	: None under recommended storage and handling conditions (see section 7). Avoid moisture in installation systems.
10.5. Incompatible materials	: For additional information on compatibility refer to ISO 11114. None.
10.6. Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
AIR LIQUIDE SINGAPORE PTE LTD HEAD OFFICE : 2 VENTURE DRIVE, VISION EXCHANGE, #22-28, SINGAPORE 608526 SPECIALGASES OFFICE, NO 24 JALAN BUROH SINGAPORE 619480	EN (English) SDS Ref.: 2018005 6/10



SDS Ref.: 2018005

## **SECTION 11: Toxicological information**

11.1. Information on toxicological effects	
Acute toxicity	: Toxicological effects not expected from this product if occupational exposure limit values are not exceeded.
	Unlike simple asphyxiants, carbon dioxide has the ability to cause death even when normal oxygen levels (20-21%) are maintained. 5% CO2 has been found to act synergistically to increase the toxicity of certain other gases (CO, NO2). CO2 has been shown to enhance the production of carboxy- or met-hemoglobin by these gases possibly due to carbon dioxide's stimulatory effects on the respiratory and circulatory systems.
	For more information, see 'EIGA Safety Info 24: Carbon Dioxide, Physiological Hazards' at www.eiga.eu.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

SINGAPORE 619480 +65 6 265 3788

Assessment	: No data available.	
EC50 48h - Daphnia magna [mg/l]	: No data available.	
EC50 72h - Algae [mg/l]	: No data available.	
LC50 96 h - fish [mg/l]	: No data available.	
12.2. Persistence and degradability		
Assessment	: No data available.	
12.3. Bioaccumulative potential		
Assessment	: No data available.	
12.4. Mobility in soil		
Assessment	: Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.	
12.5. Results of PBT and vPvB assessment		
Assessment	: No data available.	
12.6. Other adverse effects		
Other adverse effects	: No known effects from this product.	
AIR LIQUIDE SINGAPORE PTE LTD HEAD OFFICE : 2 VENTURE DRIVE, VISION EXCHANGE, #22-28, SINGAPORE 608526 SPECIALGASES OFFICE, NO 24 JALAN BUROH	EN (English) SDS Ref.: 2018005	7/10

<b>Air Liquide</b>	LASAL™68
	SDS Ref.: 2018005
Effect on the ozone layer	: None.
Effect on global warming	: Contains greenhouse gas(es).
SECTION 13: Disposal considerat	ions
13.1. Waste treatment methods	
	May be vented to atmosphere in a well ventilated place.
	Do not discharge into any place where its accumulation could be dangerous.
	Return unused product in original cylinder to supplier.
List of hazardous waste codes (from Commission Decision 2001/118/EC)	: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.
13.2. Additional information	
	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
SECTION 14: Transport information	on
14.1. UN number	
UN-No.	: 1956
14.2. UN proper shipping name	
Transport by road/rail (ADR/RID)	<sup>:</sup> COMPRESSED GAS, N.O.S. (Helium, Carbon dioxide)
Transport by air (ICAO-TI / IATA-DGR)	. Compressed gas, n.o.s. (Helium, Carbon dioxide)
Transport by sea (IMDG)	COMPRESSED GAS, N.O.S. (Helium, Carbon dioxide)
14.3. Transport hazard class(es)	
Labelling	
	2.2 : Non-flammable, non-toxic gases.
Transport by road/rail (ADR/RID)	
Class	: 2
Classification code	: 1A
Hazard identification number	
	: E - Passage forbidden through tunnels of category E
Transport by air (ICAO-TI / IATA-DGR)	
Class / Div. (Sub. risk(s))	: 2.2

AIR LIQUIDE SINGAPORE PTE LTD HEAD OFFICE : 2 VENTURE DRIVE, VISION EXCHANGE, #22-28, SINGAPORE 608526 SPECIALGASES OFFICE, NO 24 JALAN BUROH SINGAPORE 619480 +65 6 265 3788

Transport by sea (IMDG) Class / Div. (Sub. risk(s))

14.4. Packing group

Transport by sea (IMDG)

14.5. Environmental hazards

Emergency Schedule (EmS) - Fire

Transport by road/rail (ADR/RID)

Emergency Schedule (EmS) - Spillage

Transport by air (ICAO-TI / IATA-DGR)

EN (English)

: Not applicable

: Not applicable

: Not applicable

: 2.2

: F-C

: S-V

SDS Ref.: 2018005

# Air Liquide

LASAL™68

SDS Ref.: 2018005

Transport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Transport by sea (IMDG)	: None.
14.6. Special precautions for user	
Packing Instruction(s)	
Transport by road/rail (ADR/RID)	: P200
Transport by air (ICAO-TI / IATA-DGR)	
Passenger and Cargo Aircraft	: 200.
Cargo Aircraft only	: 200.
Transport by sea (IMDG)	: P200
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment.
	Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
	Before transporting product containers:
	- Ensure there is adequate ventilation.
	- Ensure that containers are firmly secured.
	- Ensure cylinder valve is closed and not leaking.
	- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
	- Ensure valve protection device (where provided) is correctly fitted.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable.

## **SECTION 15: Regulatory information**

EU-Regulations	
Restrictions on use	: None.
Seveso Directive : 2012/18/EU (Seveso III)	: Not covered.
National regulations	
National legislation	: Ensure all national/local regulations are observed.

This product is either exempt from REACH, does not meet the minimun volume threshold for a CSR or CSA has not yet been carried out.

## SECTION 16: Other information

Indication of changes

Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.

:



Abbreviations and acronyms	: ATE - Acute Toxicity Estimate
	CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
	REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
	EINECS - European Inventory of Existing Commercial Chemical Substances
	CAS# - Chemical Abstract Service number
	PPE - Personal Protection Equipment
	LC50 - Lethal Concentration to 50 % of a test population
	RMM - Risk Management Measures
	PBT - Persistent, Bioaccumulative and Toxic
	vPvB - Very Persistent and Very Bioaccumulative
	STOT- SE : Specific Target Organ Toxicity - Single Exposure
	CSA - Chemical Safety Assessment
	EN - European Standard
	UN - United Nations
	ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
	IATA - International Air Transport Association
	IMDG code - International Maritime Dangerous Goods
	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
	WGK - Water Hazard Class
	STOT - RE : Specific Target Organ Toxicity - Repeated Exposure
Training advice	: The hazard of asphyxiation is often overlooked and must be stressed during operator training.
	Receptacle under pressure.
Further information	: Classification using data from databases maintained by the European Industrial Gases Association (EIGA).
	Classification in accordance with the calculation methods of Regulation (EC) 1272/2008 CLP.

#### Full text of H- and EUH-statements

Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
H280	Contains gas under pressure; may explode if heated.

DISCLAIMER OF LIABILITY

 Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.